

View Online at <https://aerobasegroup.com/nsn/4320-01-181-3603>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Hydrocarbon fuels and oils

**Mounting Type:**

Base

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Triangular flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Triangular flange

**Current Type:**

Ac

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

50.0 gallons per minute

**Discharge Pressure:**

50.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

300.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Rotary Pump Design:**

Vane

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

1.5

**Prime Mover Power Rating:**

3.500 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400