

View Online at <https://aerobasegroup.com/nsn/4320-01-184-4280>

Prime Mover Quantity:

1

Stage Quantity:

3

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Submersible

Pump Quantity:

1

Maximum Discharge Flow Rate:

350.0 gallons per minute

Discharge Pressure:

150.0 pounds per square inch gage

Total Head:

162.000 feet

Operating Speed At Rated Capacity:

3600.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

25.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Special Features:

4.000 in. Suction w/eight 9/16 in. Holes equally spaced on 6-9/16 in. Blt cir dia; 3.000 in. Discharge w/eight 9/16 in. Holes equally spaced on 5-1/2 in. Blt cir dia

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400