

View Online at <https://aerobasegroup.com/nsn/4320-01-184-7008>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Cylinder Quantity:**

3

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded external

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded external

**Current Type:**

Ac/dc

**Environmental Protection:**

Explosion proof

**Pump Quantity:**

1

**Pumping Element Type:**

Diaphragm

**Discharge Pressure:**

800.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1725.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Fixed

**Volume Control Type:**

Hydraulic cylinder

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

3.0

**Discharge Connection Thread Size And Series/type Designator:**

0.375-18 npt

**Intake Connection Thread Size And Series/type Designator:**

0.500-14 npt

**Prime Mover Power Rating:**

0.167 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

Leakproof; cres construction; metering pump

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400