

View Online at <https://aerobasegroup.com/nsn/4320-01-184-7008>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Cylinder Quantity:

3

Intake Connection Quantity:

1

Intake Connection Type:

Threaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Current Type:

Ac/dc

Environmental Protection:

Explosion proof

Pump Quantity:

1

Pumping Element Type:

Diaphragm

Discharge Pressure:

800.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1725.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Fixed

Volume Control Type:

Hydraulic cylinder

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

3.0

Discharge Connection Thread Size And Series/type Designator:

0.375-18 npt

Intake Connection Thread Size And Series/type Designator:

0.500-14 npt

Prime Mover Power Rating:

0.167 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Leakproof; cres construction; metering pump

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400