

View Online at <https://aerobasegroup.com/nsn/4320-01-189-9883>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Wheel

Stage Quantity:

1

Intake Connection Quantity:

2

Intake Connection Type:

Quick disconnect

Discharge Connection Quantity:

2

Discharge Connection Type:

Quick disconnect

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Maximum Discharge Flow Rate:

350.0 gallons per minute

Discharge Pressure:

125.0 pounds per square inch gage

Total Head:

275.000 feet

Suction Lift:

8.000 feet

Operating Speed At Rated Capacity:

2400.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Diesel engine

Features Provided:

Self-priming

Prime Mover Power Rating:

44.000 horsepower

Special Features:

Potable water

Specification Or Standard:

li type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400