

View Online at <https://aerobasegroup.com/nsn/4320-01-192-6511>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Water, fresh

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Water cooled

Cubic Measure:

20.0000 cubic feet

Maximum Discharge Flow Rate:

60.0 gallons per minute

Total Head:

50.000 feet

Suction Lift:

50.000 feet

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

12.0

Features Provided:

Self-priming

Prime Mover Power Rating:

7.500 horsepower

Voltage In Volts:

208.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400