

View Online at <https://aerobasegroup.com/nsn/4320-01-192-8167>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

82.0 gallons per minute

Total Head:

133.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Discharge Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Prime Mover Power Rating:

2.0 horsepower

Voltage In Volts:

230.0

Phase:

Single

Special Features:

Pump can be used w/ pressure tank, air volume control tapping incl on suction side; lexan impeller; stainless steel shaft and seals; bronze wearing ring; pre-lubricated ball bearings

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400