NSN 4320-01-193-3057

Centrifugal Pump Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-193-3057

| Prime Mover Quantity: |
|---|
| 1 |
| Prime Mover Cooling Medium: |
| Air |
| Mounting Type: |
| Frame |
| Current Type: |
| Ac |
| Media For Which Designed: |
| Hydrocarbon fuels and oils |
| Environmental Protection: |
| Explosion proof |
| Cooling Method: |
| Air to air cooled |
| Maximum Discharge Flow Rate: |
| 181.0 gallons per minute |
| Discharge Pressure: |
| 1073.0 pounds per square inch gage and 1077.0 pounds per square inch gage |
| Pumping Element Operating Position: |
| Horizontal |
| Centrifugal Pump Design: |
| Axial flow |
| Centrifugal Pump Impeller Quantity: |
| 2 |
| Prime Mover Type: |
| Electric motor |
| Prime Mover Power Rating: |
| 1.000 horsepower |
| Voltage In Volts: |
| 220.0 and 460.0 |
| Phase: |
| Single |
| Frequency In Hertz: |
| 30.0 and 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A19400