

View Online at <https://aerobasegroup.com/nsn/4320-01-197-4832>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Water, salt

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Triangular flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, salt

Pump Quantity:

1

Maximum Discharge Flow Rate:

500.0 gallons per minute

Discharge Pressure:

41.0 pounds per square inch gage

Total Head:

92.000 feet

Suction Lift:

15.000 feet

Operating Speed At Rated Capacity:

3600.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

20.000 horsepower

Voltage In Volts:

440.0

Phase:

Single

Special Features:

4.000 in. Inlet w/eight 0.750 in. Diameter holes located on 9.000 in. Diameter flange; 3.000 in. Outlet w/four 0.750 in. Diameter holes located on 7.500 in. Diameter flange and having a 6.000 in. Bolt circle dia

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400