## NSN 4320-01-198-0822

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-198-0822

| Intake Connection Quantity:   |
|---|
| 1   |
| Intake Connection Type:   |
| Square flange   |
| Discharge Connection Quantity:  |
| 2   |
| Discharge Connection Type:  |
| Rectangular flange  |
| Drive Connection Type:  |
| Gear  |
| Media For Which Designed:   |
| Oil and water, fresh  |
| End Application:  |
| Harnischfeger truck-crane, omega 30 series  |
| Maximum Discharge Flow Rate:  |
| 30.0 gallons per minute   |
| Discharge Pressure:   |
| 100.0 pounds per square inch gage   |
| Operating Speed At Rated Capacity:  |
| 1200.0 revolutions per minute   |
| Pumping Element Operating Position:   |
| Horizontal  |
| Pump Rotation Direction:  |
| Clockwise   |
| Volume Control Type:  |
| Rotary  |
| Rotary Pump Design:   |
| Gear  |
| Operation Method:   |
| Powered   |
| Drive Shaft Type:   |
| Splined, involute external  |
| Drive Shaft Length:   |
| 1.248 inches  |
| Special Features:   |
| Four bolt flange, 3.000 in. Diameter inlet; outlets are four bolt flange, 1.250 in. And 1.000 in. Dia; double gear pump |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |

## NSN 4320-01-198-0822

Rotary Pump - Page 2 of 2



Fiig:

A19400