

View Online at <https://aerobasegroup.com/nsn/4320-01-199-5725>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal and threaded external

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal and threaded external

Current Type:

Ac

Media For Which Designed:

Water, fresh and water, salt

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

6.0 gallons per minute

Discharge Pressure:

4.3 pounds per square inch gage

Total Head:

10.000 feet

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Discharge Connection Thread Size And Series/type Designator:

0.375-18 npt and 0.750-11-1/2 nh

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt and 0.750-11-1/2 nh

Prime Mover Power Rating:

0.166 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Nitrile impeller

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400