

View Online at <https://aerobasegroup.com/nsn/4320-01-204-1810>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

2

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Air to air cooled

End Application:

Fresh water system onboard 110 ft class coast guard vessels

Maximum Discharge Flow Rate:

17.0 gallons per minute

Discharge Pressure:

20.0 pounds per square inch gage

Total Head:

138.600 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Volume Control Type:

Pressure compensation

Control Location:

Center

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

60.0

Discharge Connection Thread Size And Series/type Designator:

0.750-14 npt

Intake Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt and 1.000-11-1/2 npt

Prime Mover Power Rating:

0.500 horsepower

Voltage In Volts:

115.0 and 230.0

Phase:

Single

Special Features:

Frame is 56 c

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400