

View Online at <https://aerobasegroup.com/nsn/4320-01-206-1641>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

10.4 gallons per minute

**Discharge Pressure:**

8.6 pounds per square inch gage

**Operating Speed At Rated Capacity:**

1725.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Discharge Connection Thread Size And Series/type Designator:**

1.000-11-1/2 npt

**Intake Connection Thread Size And Series/type Designator:**

1.250-11-1/2 npt

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

0.500 horsepower

**Voltage In Volts:**

115.0 and 208.0 and 230.0

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400