

View Online at <https://aerobasegroup.com/nsn/4320-01-206-2611>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air and water, fresh

Mounting Type:

Base

Stage Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh or water, salt

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Water-air cooled

Cubic Measure:

2.4000 cubic feet

End Application:

Used as bilge pump onboard 210 ft wmc a and b class u. S. Coast guard vessels

Maximum Discharge Flow Rate:

100.0 gallons per minute

Total Head:

75.000 feet

Operating Speed At Rated Capacity:

3485.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

5.7

Discharge Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Prime Mover Power Rating:

5.0 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400