

View Online at <https://aerobasegroup.com/nsn/4320-01-206-2611>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air and water, fresh

**Mounting Type:**

Base

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh or water, salt

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Water-air cooled

**Cubic Measure:**

2.4000 cubic feet

**End Application:**

Used as bilge pump onboard 210 ft wmc a and b class u. S. Coast guard vessels

**Maximum Discharge Flow Rate:**

100.0 gallons per minute

**Total Head:**

75.000 feet

**Operating Speed At Rated Capacity:**

3485.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

5.7

**Discharge Connection Thread Size And Series/type Designator:**

1.250-11-1/2 npt

**Prime Mover Power Rating:**

5.0 horsepower

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400