

View Online at <https://aerobasegroup.com/nsn/4320-01-210-2499>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, salt

Environmental Protection:

Waterproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Cubic Measure:

5.0000 cubic feet

End Application:

Bilge system onboard 82 ft coast guard vessels

Maximum Discharge Flow Rate:

50.0 gallons per minute

Total Head:

75.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

6.4 and 3.2

Discharge Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Features Provided:

Self-priming

Prime Mover Power Rating:

2.0 horsepower

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

Suction strainer with removable basket and see through cover included with unit

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A19400