NSN 4320-01-211-4548

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-211-4548

| Prime Mover Quantity: |
|---|
| 1 |
| Prime Mover Cooling Medium: |
| Air |
| Stage Quantity: |
| 1 |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Threaded internal |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Current Type: |
| Ac |
| Media For Which Designed: |
| Water, fresh |
| Pump Quantity: |
| 1 |
| Cooling Method: |
| Blower cooled |
| Maximum Discharge Flow Rate: |
| 120.0 gallons per minute |
| Discharge Pressure: |
| 175.0 pounds per square inch gage |
| Total Head: |
| 20.000 feet |
| Operating Speed At Rated Capacity: |
| 1750.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Centrifugal Pump Design: |
| Radial flow |
| Centrifugal Pump Impeller Quantity: |
| 1 |
| Centrifugal Pump Impeller Suction Type: |
| Single |
| Unpackaged Unit Length: |
| 23.000 inches |
| Unpackaged Unit Width: |
| 10.6250 inches |

NSN 4320-01-211-4548

Centrifugal Pump Unit - Page 2 of 2



| Unpackaged Unit Height: |
|--|
| 14.000 inches |
| Pump Basic Material: |
| Iron |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Current Rating In Amps: |
| 6.5 and 3.2 |
| Discharge Connection Thread Size And Series/type Designator: |
| 2.000-11-1/2 npt |
| Intake Connection Thread Size And Series/type Designator: |
| 2.000-11-1/2 npt |
| Prime Mover Power Rating: |
| 1.0 horsepower |
| Voltage In Volts: |
| 115.0 and 230.0 |
| Phase: |
| Single |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A19400 |
| |