

View Online at <https://aerobasegroup.com/nsn/4320-01-211-8399>

**Key Length:**

622.00 millimeters

**Key Width:**

241.00 millimeters

**End Application:**

6920-01-185-9279

**Key Height:**

252.00 millimeters

**Product Name:**

Pump/motor/reservoir/valve unit

**Special Features:**

P/n m-405 (on source control drwg) has been replaced by p/n m-4505

**Functional Description:**

4-way/3-position solenoid operated do3 valve, standard tandem center shown, .250" npt outlets, horizontal mounting standard, vertical mounting (motor-up) optional

**Supplementary Features:**

115/230 vac, 60cy, single phase, 2000 psi/rv, solenoid valve, spool type, 4 way tandem center with standard nfpa doi interface, 12 vdc coil, 3.5 amp, 1800 to 1900 psi, operational flow rate at 2000psi, 1.9gpm, motor: single phase 2hp, 60 cycles, 3450 rpm, lock rotor kilovolt amp at vac 130amps, at 230 vac 65 amps, temperature rise: 75c, maximum ambient temperature: 40c, current load at 115vac: 20.4 amps, at 230vac: 10.2amps

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T103-f