## NSN 4320-01-211-8399

Hydraulic Motor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-211-8399

Key Length:
622.00 millimeters
Key Width:
241.00 millimeters
End Application:
6920-01-185-9279
Key Height:
252.00 millimeters
Product Name:
Pump/motor/reservoir/valve unit
Special Features:
P/n m-405 (on source control drwg) has been replaced by p/n m-4505
Functional Description:
4-way/3-position solenoid operated do3 valve, standard tandem center shown, .250" npt outlets, horizontal mounting standard, vertical
mounting (motor-up) optional
Supplementary Features:
115/230 vac, 60cy, single phase, 2000 psi/rv, solenoid valve, spool type, 4 way tandem center with standard nfpa doi interface, 12 vdc
coil, 3.5 amp, 1800 to 1900 psi, operational flow rate at 2000psi, 1.9gpm, motor: single phase 2hp, 60 cycles, 3450 rpm, lock rotor
kilovolt amp at vac 130amps, at 230 vac 65 amps, temperature rise: 75c, maximum ambient temperature: 40c, current load at 115vac:
20.4 amps, at 230vac: 10.2amps
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T103-f