

View Online at <https://aerobasegroup.com/nsn/4320-01-212-6834>

**Mounting Type:**

Base

**Intake Connection Quantity:**

2

**Intake Connection Type:**

Rectangular flange and threaded internal

**Discharge Connection Quantity:**

2

**Discharge Connection Type:**

Threaded internal and threaded internal

**Drive Connection Type:**

Close coupled

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Maximum Discharge Flow Rate:**

42.0 gallons per minute and 28.0 gallons per minute

**Discharge Pressure:**

2900.0 pounds per square inch gage and 3000.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

2500.0 revolutions per minute and 3300.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Clockwise

**Rotary Pump Design:**

Gear

**Operation Method:**

Powered

**Drive Shaft Type:**

Plain round

**Drive Shaft End Diameter:**

0.875 inches

**Drive Shaft Length:**

2.250 inches

**Discharge Connection Thread Size And Series/type Designator:**

1.062-12 un and 0.875-14 unf

**Intake Connection Thread Size And Series/type Designator:**

1.625-12 un

**Special Features:**

Tandem pump; pad mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400