

View Online at <https://aerobasegroup.com/nsn/4320-01-212-6834>

Mounting Type:

Base

Intake Connection Quantity:

2

Intake Connection Type:

Rectangular flange and threaded internal

Discharge Connection Quantity:

2

Discharge Connection Type:

Threaded internal and threaded internal

Drive Connection Type:

Close coupled

Media For Which Designed:

Hydrocarbon fuels and oils

Maximum Discharge Flow Rate:

42.0 gallons per minute and 28.0 gallons per minute

Discharge Pressure:

2900.0 pounds per square inch gage and 3000.0 pounds per square inch gage

Operating Speed At Rated Capacity:

2500.0 revolutions per minute and 3300.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Clockwise

Rotary Pump Design:

Gear

Operation Method:

Powered

Drive Shaft Type:

Plain round

Drive Shaft End Diameter:

0.875 inches

Drive Shaft Length:

2.250 inches

Discharge Connection Thread Size And Series/type Designator:

1.062-12 un and 0.875-14 unf

Intake Connection Thread Size And Series/type Designator:

1.625-12 un

Special Features:

Tandem pump; pad mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400