

View Online at <https://aerobasegroup.com/nsn/4320-01-217-0025>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Oval flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Oval flange

Current Type:

Ac

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

21.7 gallons per minute and 4.8 gallons per minute

Total Head:

1.000 feet and 7.000 feet

Operating Speed At Rated Capacity:

1500.0 revolutions per minute

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Length:

9.688 inches

Unpackaged Unit Width:

4.8120 inches

Unpackaged Unit Height:

6.312 inches

Pump Basic Material:

Iron

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

0.3

Prime Mover Power Rating:

0.05 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Line mtd; flanges must be ordered separately

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400