## NSN 4320-01-217-2646

Reciprocating Pump Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-217-2646

Prime Mover Quantity:
1
Mounting Type:
Base
Cylinder Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Media For Which Designed:
Air
Power Drive Operating Pressure:
100.0 pounds per square inch gage
Pump Quantity:
1
Pumping Element Type:
Dieton
Piston
Discharge Pressure:
· · · · · · · · · · · · · · · · · · ·
Discharge Pressure:
Discharge Pressure: 6100.0 pounds per square inch gage
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type:
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type: Fixed
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type: Fixed Prime Mover Type:
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type: Fixed Prime Mover Type: Pneumatic motor
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type: Fixed Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator:
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type: Fixed Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 0.250-18 npt
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type: Fixed Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 0.250-18 npt Intake Connection Thread Size And Series/type Designator:
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type: Fixed Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 0.250-18 npt Intake Connection Thread Size And Series/type Designator: 0.250-18 npt
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type: Fixed Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 0.250-18 npt Intake Connection Thread Size And Series/type Designator: 0.250-18 npt Shelf Life:
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type: Fixed Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 0.250-18 npt Intake Connection Thread Size And Series/type Designator: 0.250-18 npt Shelf Life: N/a
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type: Fixed Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 0.250-18 npt Intake Connection Thread Size And Series/type Designator: 0.250-18 npt Shelf Life: N/a Unit Of Measure:
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type: Fixed Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 0.250-18 npt Intake Connection Thread Size And Series/type Designator: 0.250-18 npt Shelf Life: N/a Unit Of Measure:
Discharge Pressure: 6100.0 pounds per square inch gage Reciprocating Stroke Type: Fixed Prime Mover Type: Pneumatic motor Discharge Connection Thread Size And Series/type Designator: 0.250-18 npt Intake Connection Thread Size And Series/type Designator: 0.250-18 npt Shelf Life: N/a Unit Of Measure: Demilitarization: