

View Online at <https://aerobasegroup.com/nsn/4320-01-224-4715>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

6

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Dc

Media For Which Designed:

Water, salt

Pump Quantity:

1

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

230.0 gallons per minute

Suction Lift:

25.000 feet

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

6

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

497.0

Features Provided:

Self-priming

Criticality Code Justification:

Zzzy

Voltage In Volts:

250.0

Reference Number Differentiating Characteristics:

Items that support a level i or subsafe critical system/component that has undergone quality assurance during the acquisition process and requires objective quality evidence (oqe) traceable to permanent marking on the material

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400