NSN 4320-01-225-9012

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-225-9012

| Prime Mover Quantity: | | |
|---|--|--|
| 1 | | |
| Prime Mover Cooling Medium: | | |
| Air | | |
| Stage Quantity: | | |
| 1 | | |
| Intake Connection Quantity: | | |
| 1 | | |
| Intake Connection Type: | | |
| Round flange | | |
| Discharge Connection Quantity: | | |
| 1 | | |
| Discharge Connection Type: | | |
| Round flange | | |
| Current Type: | | |
| Ac | | |
| Media For Which Designed: | | |
| Water, salt | | |
| Pump Quantity: | | |
| 1 | | |
| Cooling Method: | | |
| Blower cooled | | |
| Maximum Discharge Flow Rate: | | |
| 1000.0 gallons per minute | | |
| Discharge Pressure: | | |
| 66.0 pounds per square inch gage | | |
| Total Head: | | |
| 150.000 feet | | |
| Operating Speed At Rated Capacity: | | |
| 3600.0 revolutions per minute | | |
| Pumping Element Operating Position: | | |
| Horizontal | | |
| Centrifugal Pump Impeller Quantity: | | |
| 1 | | |
| Centrifugal Pump Impeller Suction Type: | | |
| Single | | |
| Prime Mover Type: | | |
| Electric motor | | |
| Prime Mover Power Rating: | | |
| 150.000 horsepower | | |
| Voltage In Volts: | | |
| 440.0 | | |

NSN 4320-01-225-9012

Centrifugal Pump Unit - Page 2 of 2



| \mathbf{r} | naea. | |
|--------------|-------|--|
| | Hase. | |

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400