## NSN 4320-01-226-0209

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-226-0209

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Base
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Water, fresh
Pump Quantity:
1
Cooling Method:
Air to air cooled
Maximum Discharge Flow Rate:
30.0 gallons per minute
Total Head:
208.000 feet
Suction Lift:
10.000 feet
Operating Speed At Rated Capacity:
3500.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Mixed flow
Centrifugal Pump Impeller Quantity:
1
Unpackaged Unit Length:
27.188 inches
Unpackaged Unit Width:
9.6250 inches
Unpackaged Unit Height:
12.500 inches

## NSN 4320-01-226-0209

Centrifugal Pump Unit - Page 2 of 2



Prime Mover Type:
Electric motor
Inclosure Type:
Partially enclosed
Prime Mover Power Rating:
7.50 horsepower
Voltage In Volts:
440.0
Phase:
Three
Special Features:
14.250in.O/a w; for potable water
Erosuonov In Hortz
Frequency In Hertz:
60.0
•
60.0
60.0  Reference Number Differentiating Characteristics:
Reference Number Differentiating Characteristics: Non magnetic permeability of 2.0 pct or less
Reference Number Differentiating Characteristics: Non magnetic permeability of 2.0 pct or less Shelf Life:
Reference Number Differentiating Characteristics: Non magnetic permeability of 2.0 pct or less Shelf Life: N/a
Reference Number Differentiating Characteristics: Non magnetic permeability of 2.0 pct or less Shelf Life: N/a
Reference Number Differentiating Characteristics: Non magnetic permeability of 2.0 pct or less Shelf Life: N/a Unit Of Measure:
Reference Number Differentiating Characteristics: Non magnetic permeability of 2.0 pct or less Shelf Life: N/a Unit Of Measure: Demilitarization: