

View Online at <https://aerobasegroup.com/nsn/4320-01-226-7109>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Cylinder Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Environmental Protection:

Explosion proof

Pump Quantity:

1

Pumping Element Type:

Diaphragm

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

0.05 gallons per minute

Discharge Pressure:

1100.0 pounds per square inch gage

Operating Speed At Rated Capacity:

117.0 strokes per minute

Pumping Element Operating Position:

Vertical

Pump Reciprocating Design:

Single acting

Reciprocating Stroke Type:

Variable

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Discharge Connection Thread Size And Series/type Designator:

0.250-18 npt

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt

Prime Mover Power Rating:

0.333 horsepower

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400