

View Online at <https://aerobasegroup.com/nsn/4320-01-226-7109>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Cylinder Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Environmental Protection:**

Explosion proof

**Pump Quantity:**

1

**Pumping Element Type:**

Diaphragm

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

0.05 gallons per minute

**Discharge Pressure:**

1100.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

117.0 strokes per minute

**Pumping Element Operating Position:**

Vertical

**Pump Reciprocating Design:**

Single acting

**Reciprocating Stroke Type:**

Variable

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Discharge Connection Thread Size And Series/type Designator:**

0.250-18 npt

**Intake Connection Thread Size And Series/type Designator:**

0.375-18 npt

**Prime Mover Power Rating:**

0.333 horsepower

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400