NSN 4320-01-228-1061

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-228-1061

Prime Mover Quantity:		
1		
Prime Mover Cooling Medium:		
Air		
Stage Quantity:		
1		
Intake Connection Quantity:		
1		
Intake Connection Type:		
Round flange		
Discharge Connection Quantity:		
1		
Discharge Connection Type:		
Round flange		
Current Type:		
Ac		
Media For Which Designed:		
Water, salt		
Pump Quantity:		
1		
Cooling Method:		
Blower cooled		
Maximum Discharge Flow Rate:		
245.0 gallons per minute		
Discharge Pressure:		
34.0 pounds per square inch gage		
Total Head:		
78.000 feet		
Operating Speed At Rated Capacity:		
1780.0 revolutions per minute		
Pumping Element Operating Position:		
Horizontal		
Centrifugal Pump Impeller Quantity:		
1		
Prime Mover Type:		
Electric motor		
Inclosure Type:		
Fully enclosed		
Prime Mover Power Rating:		
7.000 horsepower		
Voltage In Volts:		
440.0		

NSN 4320-01-228-1061

Centrifugal Pump Unit - Page 2 of 2



\mathbf{r}	naea.	
	Hase.	

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400