

View Online at <https://aerobasegroup.com/nsn/4320-01-230-6646>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

2

Intake Connection Type:

Threaded internal and threaded external

Discharge Connection Quantity:

2

Discharge Connection Type:

Threaded internal and threaded external

Current Type:

Dc

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

1.9 gallons per minute

Discharge Pressure:

4.3 pounds per square inch gage

Total Head:

10.000 feet

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Current Rating In Amps:

3.5

Discharge Connection Thread Size And Series/type Designator:

0.375-18 npt and 0.750-14 npsh

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt and 0.750-14 npsh

Features Provided:

Self-priming

Voltage In Volts:

12.0

Special Features:

Furnished w/neoprene impeller

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400