

View Online at <https://aerobasegroup.com/nsn/4320-01-233-3429>

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Square flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Square flange

**Drive Connection Type:**

Close coupled

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Cubic Measure:**

0.0778 cubic feet

**End Application:**

Power pack assembly of the fin stabilizer, p5352501-a, 110 ft class coast guard vessels

**Maximum Discharge Flow Rate:**

6.0 gallons per minute

**Discharge Pressure:**

4000.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

2800.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Clockwise

**Rotary Pump Design:**

Vane

**Operation Method:**

Powered

**Drive Shaft Type:**

Key type, external

**Drive Shaft End Diameter:**

0.875 inches

**Drive Shaft Length:**

2.810 inches

**Special Features:**

Suction part 1.500 ins. Pressurepart 1.000 ins.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400