

View Online at <https://aerobasegroup.com/nsn/4320-01-234-8116>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Liquid

**Environmental Protection:**

Dripproof

**Pump Quantity:**

1

**Cooling Method:**

Self ventilated

**Accessory Components:**

Electric power cable

**Cubic Measure:**

0.1000 cubic feet

**End Application:**

6530-01-134-3182 thermoregulator, patient

**Maximum Discharge Flow Rate:**

7.6 gallons per minute

**Total Head:**

19.000 feet

**Operating Speed At Rated Capacity:**

3400.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Operation Relationship Design:**

Simultaneous

**Unpackaged Unit Length:**

7.750 inches

**Unpackaged Unit Width:**

3.750 inches

**Unpackaged Unit Height:**

5.000 inches

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Current Rating In Amps:**

1.35

**Discharge Connection Thread Size And Series/type Designator:**

0.375-18 nptf

**Intake Connection Thread Size And Series/type Designator:**

0.500-14 nptf

**Prime Mover Power Rating:**

0.040 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

Base w/pump, motor trailer mounted

**Frequency In Hertz:**

50.0 and 60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400