

View Online at <https://aerobasegroup.com/nsn/4320-01-234-8116>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Liquid

Environmental Protection:

Drip-proof

Pump Quantity:

1

Cooling Method:

Self ventilated

Accessory Components:

Electric power cable

Cubic Measure:

0.1000 cubic feet

End Application:

6530-01-134-3182 thermoregulator, patient

Maximum Discharge Flow Rate:

7.6 gallons per minute

Total Head:

19.000 feet

Operating Speed At Rated Capacity:

3400.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

7.750 inches

Unpackaged Unit Width:

3.750 inches

Unpackaged Unit Height:

5.000 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Open

Current Rating In Amps:

1.35

Discharge Connection Thread Size And Series/type Designator:

0.375-18 nptf

Intake Connection Thread Size And Series/type Designator:

0.500-14 nptf

Prime Mover Power Rating:

0.040 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Base w/pump, motor trailer mounted

Frequency In Hertz:

50.0 and 60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400