NSN 4320-01-238-0786

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-238-0786

Drima Mayor Ovantitus
Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Stage Quantity:
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Dc
Media For Which Designed:
Water, fresh
Pump Quantity:
1
Cooling Method:
Air to air cooled
Maximum Discharge Flow Rate:
9.0 gallons per minute
Discharge Pressure:
4.0 pounds per square inch gage
Operating Speed At Rated Capacity:
3400.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Mixed flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Current Rating In Amps:

4.3

NSN 4320-01-238-0786

Centrifugal Pump Unit - Page 2 of 2



Voltage In Volt	ts:
-----------------	-----

24.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400