NSN 4320-01-238-0787

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-238-0787

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Water, fresh
Pump Quantity:
1
Cooling Method:
Blower cooled
Maximum Discharge Flow Rate:
18.0 gallons per minute
Operating Speed At Rated Capacity:
3500.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Centrifugal Pump Design:
Mixed flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Prime Mover Power Rating:
3.000 horsepower
Voltage In Volts:
230.0 and 460.0

NSN 4320-01-238-0787

Centrifugal Pump Unit - Page 2 of 2



\mathbf{r}	naea.	
	Hase.	

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400