

View Online at <https://aerobasegroup.com/nsn/4320-01-241-4394>

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Drive Connection Type:

Flexible coupled

Media For Which Designed:

Water, fresh

End Application:

Aux boiler sdw-350m aboard 400 ft wagb c.G. Vessels

Maximum Discharge Flow Rate:

50.0 gallons per minute

Discharge Pressure:

25.0 pounds per square inch gage

Total Head:

100.000 feet

Suction Lift:

20.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Clockwise

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Double

Drive Shaft Type:

Key type, external

Drive Shaft End Diameter:

0.875 inches

Drive Shaft Length:

2.187 inches

Discharge Connection Thread Size And Series/type Designator:

2.000-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

2.500-8 npt

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400