

View Online at <https://aerobasegroup.com/nsn/4320-01-242-1336>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Water, fresh

**Stage Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Water, fresh

**Environmental Protection:**

Waterproof

**Pump Quantity:**

1

**Cooling Method:**

Water cooled

**Maximum Discharge Flow Rate:**

60.0 gallons per minute and 41.66 gallons per minute and 26.66 gallons per minute

**Total Head:**

5.000 feet and 10.000 feet and 15.000 feet

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Unpackaged Unit Height:**

14.500 inches

**Pump Basic Material:**

Iron

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

2.2

**Discharge Connection Thread Size And Series/type Designator:**

1.500-11-1/2 npt

**Prime Mover Power Rating:**

0.333 horsepower

**Voltage In Volts:**

115.0

**Phase:**

Single

**Special Features:**

Stainless steel motor casing acts as float to activate switch; turn-on level 12.000 in.; turn-off level 8.000 in.; maximum water temp 160 degrees f; pump 10.125 in. Dia; incl 10.000 ft waterproof cord and 3-prong plug, t-carrying handle

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400