

View Online at <https://aerobasegroup.com/nsn/4320-01-242-1336>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Water, fresh

Stage Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Waterproof

Pump Quantity:

1

Cooling Method:

Water cooled

Maximum Discharge Flow Rate:

60.0 gallons per minute and 41.66 gallons per minute and 26.66 gallons per minute

Total Head:

5.000 feet and 10.000 feet and 15.000 feet

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Height:

14.500 inches

Pump Basic Material:

Iron

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

2.2

Discharge Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Prime Mover Power Rating:

0.333 horsepower

Voltage In Volts:

115.0

Phase:

Single

Special Features:

Stainless steel motor casing acts as float to activate switch; turn-on level 12.000 in.; turn-off level 8.000 in.; maximum water temp 160 degrees f; pump 10.125 in. Dia; incl 10.000 ft waterproof cord and 3-prong plug, t-carrying handle

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400