

View Online at <https://aerobasegroup.com/nsn/4320-01-248-0899>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Skid

Stage Quantity:

1

Intake Connection Quantity:

1

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded external

Media For Which Designed:

Water, fresh

Pump Quantity:

1

Maximum Discharge Flow Rate:

60.0 gallons per minute

Discharge Pressure:

171.0 pounds per square inch gage

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Unpackaged Unit Length:

28.000 inches

Unpackaged Unit Width:

20.0000 inches

Unpackaged Unit Height:

16.000 inches

Pump Basic Material:

Aluminum

Prime Mover Type:

Gasoline engine

Discharge Connection Thread Size And Series/type Designator:

1.500-9 nh

Features Provided:

Self-priming

Prime Mover Power Rating:

8.000 horsepower

Special Features:

Usda forest service acceptance specification 5100-00275; pump is supported on water source by a float; flood-proof; automatic float ty
throttle; suction hose not required; uses regular gas and oil; throws water stream up to 85 feet; total hd-394 feet; built-in suction screen

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400