

View Online at <https://aerobasegroup.com/nsn/4320-01-248-0899>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Skid

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded external

**Media For Which Designed:**

Water, fresh

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

60.0 gallons per minute

**Discharge Pressure:**

171.0 pounds per square inch gage

**Pumping Element Operating Position:**

Vertical

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Unpackaged Unit Length:**

28.000 inches

**Unpackaged Unit Width:**

20.0000 inches

**Unpackaged Unit Height:**

16.000 inches

**Pump Basic Material:**

Aluminum

**Prime Mover Type:**

Gasoline engine

**Discharge Connection Thread Size And Series/type Designator:**

1.500-9 nh

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

8.000 horsepower

**Special Features:**

Usda forest service acceptance specification 5100-00275; pump is supported on water source by a float; flood-proof; automatic float ty  
throttle; suction hose not required; uses regular gas and oil; throws water stream up to 85 feet; total hd-394 feet; built-in suction screen

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A19400