NSN 4320-01-248-2700

Spring Loaded Shaft Seal Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-01-248-2700

General Description:

Shelf Life:	
spring loaded; speed: 38000 rpm; oil: mil-l-7808 and mil-l-23699, temp: air, -65 to 1000 degrees f; oil, -65 to 300 degrees f; to	urbine seal
length 0.529 in. Min and 0.531 in. Max; 2.046 in. Min and 2.048 in. Maximum od; bore 1.25 in. Dia; carbon nose face width 0.529 in. Min and 0.531 in. Max; 2.046 in. Min and 2.048 in. Maximum od; bore 1.25 in. Dia; carbon nose face width 0.529 in. Min and 0.531 in. Max; 2.046 in. Min and 2.048 in. Maximum od; bore 1.25 in. Dia; carbon nose face width 0.529 in. Min and 0.531 in. Max; 2.046 in. Min and 2.048 in. Maximum od; bore 1.25 in. Dia; carbon nose face width 0.529 in. Min and 0.531 in. Max; 2.046 in. Min and 2.048 in. Maximum od; bore 1.25 in. Dia; carbon nose face width 0.529 in. Min and 0.531 in. Max; 2.046 in. Min and 0.540 in.	0.055-0.065

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A23900