## NSN 4320-01-249-6625

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-249-6625

Thread Direction:
Right-hand
Torque Load Rating:
159.2 inch-pounds
Key Length:
1.000 inches
Mounting Type:
Bracket or face
Key Width:
0.250 inches
Mounting Hole Diameter:
0.375 inches
Mounting Hole Quantity:
4
Thread Size:
1.062-12 and 1.062-12 and 0.750-16
Shaft Diameter:
0.999 inches
Operating Speed At Rated Capacity In Rpm:
460.0
Mounting Bolt Circle Diameter:
3.250 inches
Drive Shaft Type:
Keyed
Housing Material:
Aluminum or steel
Screw Thread Series Designator:
Unf
Shaft Rotation Direction:
Clockwise and counterclockwise
Thread Location:
Internal
Shaft Protrusion Length:
1.620 inches
Connection Quantity:
1 and 1 and 1
Connection Type:
Inlet and outlet and drain
Maximum Working Pressure Rating At Specificationified Tempurature Range:
1250.0 psi w/ temp range unrated
Connection Design:
Threaded

## **NSN 4320-01-249-6625** Hydraulic Motor - Page 2 of 2



Key Height:
0.125 inches
Displacement Type:
Constant
Constant Displacement Per Revolution:
10.000 cubic inches
Connection Government Specification/std:
All connections sae standard
Housing Surface Treatment:
Cadmium plated
Special Features:
Viton seals
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T103-f