

View Online at <https://aerobasegroup.com/nsn/4320-01-250-1830>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Ac

**Media For Which Designed:**

Hydrocarbon fuels and oils and liquid and water, fresh and water, salt

**Pump Quantity:**

1

**Cooling Method:**

Blower cooled

**Maximum Discharge Flow Rate:**

250.0 gallons per minute

**Total Head:**

105.000 feet

**Operating Speed At Rated Capacity:**

3500.0 revolutions per minute

**Centrifugal Pump Design:**

Mixed flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Pump Basic Material:**

Iron

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

32.4 and 16.2

**Prime Mover Power Rating:**

10.0 horsepower

**Voltage In Volts:**

230.0 and 460.0

**Phase:**

Three

**Special Features:**

Suction 3.00 in. Dia, discharge 2.50 in. Dia; carbon/ceramic viton seals

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400