

View Online at <https://aerobasegroup.com/nsn/4320-01-250-1830>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils and liquid and water, fresh and water, salt

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

250.0 gallons per minute

Total Head:

105.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Pump Basic Material:

Iron

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

32.4 and 16.2

Prime Mover Power Rating:

10.0 horsepower

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

Suction 3.00 in. Dia, discharge 2.50 in. Dia; carbon/ceramic viton seals

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400