

View Online at <https://aerobasegroup.com/nsn/4320-01-254-0446>

**Mounting Type:**

Flange

**Discharge Connection Quantity:**

2

**Discharge Connection Type:**

Square flange

**Drive Connection Type:**

Rigid coupled

**Media For Which Designed:**

Oil

**Maximum Discharge Flow Rate:**

10.1 gallons per minute

**Discharge Pressure:**

65.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

5880.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Pump Rotation Direction:**

Clockwise

**Rotary Pump Design:**

Gear

**Operation Method:**

Powered

**Criticality Code Justification:**

Feat

**Special Features:**

Fscap; 6 inlet conn; 3 ea triangular flg, 1 ea oval flg, 1 ea irregular flg (which accom 2 inlets); 1 of 2 outlet conn is irregular flg; ext surfaces alum; oil spec: mill7808 or 23699; 2 jets in pump shaft prov pos lub to splines of adjacent hyd & fuel pumps

**Surface Treatment:**

Anodize

**Surface Treatment:**

Anodized, mil-a-8625

**Reference Number Differentiating Characteristics:**

As differentiated by the source control dwg no. 9338m65p07

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A19400