

View Online at <https://aerobasegroup.com/nsn/4320-01-254-9660>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Self ventilated

Cubic Measure:

1.5000 cubic feet

End Application:

Fresh water pumping system onboard 110 and 378 ft coast guard vessels

Maximum Discharge Flow Rate:

94.0 gallons per minute

Discharge Pressure:

34.0 pounds per square inch gage

Total Head:

80.000 feet

Operating Speed At Rated Capacity:

3450.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Axial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

5.2 and 2.6

Discharge Connection Thread Size And Series/type Designator:

1.250-11-1/2 npt

Intake Connection Thread Size And Series/type Designator:

1.500-11-1/2 npt

Prime Mover Power Rating:

1.5 horsepower

Voltage In Volts:

220.0 and 440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400