

View Online at <https://aerobasegroup.com/nsn/4320-01-257-0819>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Water, salt

Mounting Type:

Frame

Stage Quantity:

1

Intake Connection Quantity:

1

Discharge Connection Quantity:

1

Current Type:

Ac

Media For Which Designed:

Water, salt

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Water cooled

End Application:

Buffalo pump co. 6x8 sl pump

Discharge Pressure:

150.0 pounds per square inch gage

Operating Speed At Rated Capacity:

1750.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

40.0 horsepower

Voltage In Volts:

444.0

Phase:

Three

Special Features:

Impeller 11.125 in.Dia; 1575.0 gal/min; 160.0 ft total head

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400