NSN 4320-01-257-2162

Centrifugal Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-257-2162

| Mounting Type: |
|--|
| Base |
| Stage Quantity: |
| 1 |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Threaded internal |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Media For Which Designed: |
| Liquid and hydrocarbon fuels and oils |
| Maximum Discharge Flow Rate: |
| 74.0 gallons per minute |
| Discharge Pressure: |
| 33.0 pounds per square inch gage |
| Total Head: |
| 90.000 feet |
| Operating Speed At Rated Capacity: |
| 4000.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Pump Rotation Direction: |
| Counterclockwise |
| Centrifugal Pump Design: |
| Mixed flow |
| Centrifugal Pump Impeller Quantity: |
| 1 |
| Centrifugal Pump Impeller Suction Type: |
| Single |
| Drive Shaft Type: |
| Key type, external |
| Drive Shaft End Diameter: |
| 0.063 inches |
| Drive Shaft Length: |
| 1.720 inches |
| Discharge Connection Thread Size And Series/type Designator: |
| 1.500-11-1/2 npt |
| Intake Connection Thread Size And Series/type Designator: |

1.500-11-1/2 npt

NSN 4320-01-257-2162

Centrifugal Pump - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400