NSN 4320-01-257-8153

Rotary Pump - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-01-257-8153

| Intake Connection Quantity: |
|---|
| 1 |
| |
| Intake Connection Type: |
| Round flange |
| Discharge Connection Quantity: |
| 1 Discharge Connection Towns |
| Discharge Connection Type: |
| Round flange |
| Drive Connection Type: |
| Flexible coupled |
| Cubic Measure: |
| 2.5800 cubic feet |
| End Application: |
| Prelube pump for the reduction gear onboard 210 ft "b" class wmec coast guard cutters |
| Maximum Discharge Flow Rate: |
| 32.0 gallons per minute |
| Discharge Pressure: |
| 43.0 pounds per square inch gage |
| Total Head: |
| 99.000 feet |
| Operating Speed At Rated Capacity: |
| 1800.0 revolutions per minute |
| Pumping Element Operating Position: |
| Horizontal |
| Pump Rotation Direction: |
| Clockwise |
| Rotary Pump Design: |
| Gear |
| Operation Method: |
| Powered |
| Drive Shaft Type: |
| Machine keyway |
| Drive Shaft End Diameter: |
| 0.750 inches |
| Drive Shaft Length: |
| 2.120 inches |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 4320-01-257-8153

Rotary Pump - Page 2 of 2



Fiig:

A19400