

View Online at <https://aerobasegroup.com/nsn/4320-01-257-8726>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Frame

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Media For Which Designed:

Water, distilled

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

42.0 gallons per minute

Discharge Pressure:

200.0 pounds per square inch gage

Total Head:

40.000 feet

Operating Speed At Rated Capacity:

3575.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Mixed flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

60.0

Prime Mover Power Rating:

7.500 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400